STAHL+BAND





 $\label{thm:continuous} \begin{tabular}{ll} Teable aux II shown in Anchor Process with additives. \it Designed by Bruce Rowe for Anchor Ceramics. \it Teable aux II shown in Anchor Process with additives. \it Designed by Bruce Rowe for Anchor Ceramics. \it Teable aux II shown in Anchor Process with additives. \it Designed by Bruce Rowe for Anchor Ceramics. \it Teable aux II shown in Anchor Process with additives. \it Designed by Bruce Rowe for Anchor Ceramics. \it Teable aux II shown in Anchor Process with additives. \it Designed by Bruce Rowe for Anchor Ceramics. \it Teable aux II shown in Anchor Process with additives. \it Designed by Bruce Rowe for Anchor Ceramics. \it Teable aux II shown in Anchor Ceramics. \it Tea$

TABLEAUX III

Standard Dimensions	Overall: 48" L x 24 %" W x 14 ¼" H	
	Leg: 1 ½" DIA	
	Plinth I: 16 %" L x 6 ½" W x 1 %" H	
Details	Stoneware ceramic tile, 304-grade stainless steel base and legs, black patina, epoxy grout, and wax finish.	*Unique 1 of 1 *Outdoor appropriate
	Anchor process with additives.	
List Price *	Contact for pricing.	* List pricing is subject to change and does not include shipping.

STAHL+BAND

Care Instructions

- The legs of each Tableaux are removable for transportation. They screw in securely to the tabletop and have a rubber foot for floor protection.
- Do not lift or rotate the table using the legs.
- Do not transport the table on edge or with the tiled surface facing down.
- Ceramic surfaces will vary in colour range, tonal quality, density, and porosity.
- Tableaux is made from high fired stoneware clay bodies. Some surfaces have a glaze finish; others are left unglazed to celebrate the inherent qualities of the clay body they have been made with.
- Unglazed and less glossy surfaces will be more susceptible to marks and staining but all unglazed Tableaux have been treated with a penetrating sealer.
- During transport and installation, we recommend the installer wear disposable gloves to stop grease and dirt transfer.
- Gently wipe the ceramic surface using warm, soapy water and a clean, lint-free, soft cloth wrung dry. Leave to dry before placing the plinth or other objects on the table.
- Stubborn marks on the ceramic surface can be removed with methylated spirits and a clean lint-free, soft cloth. Do not use methylated spirits on the metal table base or legs.
- Do not scrub, use scourers, steel wool, or abrasive soaps and cleaners.
- Do not use high pressure hose cleaning equipment.
- When dusting, lightly wipe with a clean lint-free, soft cloth or other dusting brush.
- Handle powder coated surfaces with care.